




Slither® Sewer Cleaning Hoses



SLITHER® 2,500 PSI

SLSPOR Series



A yellow polyolefin tube, single high tensile synthetic fiber braid reinforcement and abrasion resistant slick orange polyether-urethane cover.

Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLSPOR-10	5/8	16.0	0.96	24.4	2500	172.4	6250	430.9	4.00	101.6	0.19
SLSPOR-12	3/4	19.1	1.18	30.0	2500	172.4	6250	430.9	5.00	127.0	0.28
SLSPOR-16	1	25.4	1.46	37.1	2500	172.4	6250	430.9	6.00	152.4	0.40
SLSPOR-20	1 1/4	32.0	1.80	45.7	2500	172.4	6250	430.9	8.00	203.2	0.59
SLSPOR-24	1 1/2	38.1	2.18	55.4	2500	172.4	6250	430.9	15.00	381.0	0.94



SLITHER® 3,000 PSI

SLHPBU Series



A yellow polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant slick blue polyether-urethane cover.

Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLHPBU-12	3/4	19.1	1.18	30.0	3000	206.8	7500	517.1	5.00	127.0	0.29
SLHPBU-16	1	25.4	1.48	37.6	3000	206.8	7500	517.1	8.00	203.2	0.41
SLHPBU-20	1 1/4	31.2	1.80	45.7	3000	206.8	7500	517.1	10.00	234.0	0.59



Slither® Jetting Line Hoses



SLITHER® 4,000 PSI

SLGR Series



A yellow seamless polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant slick green polyether-urethane cover.

Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLGR-12	3/4	19.1	1.30	33.0	4000	275.8	10000	689.5	5.00	127.0	0.41
SLGR-16	1	25.4	1.63	41.4	4000	275.8	10000	689.5	8.00	152.4	0.65

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



Enquire now!
sales@kuriyama.com.au
Ph: 02 9651 1233

Slither® Jetting Line Hoses



SLITHER® 3,000 PSI SLBU Series



A yellow seamless thermoplastic tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant **slick** blue polyurethane cover.

Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +190°F (+87°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLBU-08	1/2	12.8	0.83	21.2	3000	206.8	7500	517.1	4.00	101.6	0.16



SLITHER® 4,000 PSI SLGR Series



A yellow seamless thermoplastic tube, single or double high tensile synthetic fiber braid reinforcement and abrasion resistant **slick** green polyurethane cover.

Nominal Specifications

*** Service Temperature Range 12, 16: -40°F (-40°C) to +150°F (+66°C)
** Service Temperature Range 02, 03: -40°F (-40°C) to +160°F (+71°C)
* Service Temperature Range 04, 06, 08: -40°F (-40°C) to +190°F (+87°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
**SLGR-02	1/8	3.6	0.32	8.2	4000	275.8	10000	689.5	1.25	31.2	0.04
**SLGR-03	3/16	4.8	0.41	10.5	4000	275.8	10000	689.5	1.75	44.5	0.05
*SLGR-04	1/4	6.4	0.50	12.6	4000	275.8	10000	689.5	2.50	63.5	0.06
*SLGR-06	3/8	9.7	0.65	16.5	4000	275.8	10000	689.5	3.00	76.2	0.11
*SLGR-08	1/2	12.8	0.83	21.2	4000	275.8	10000	689.5	4.00	101.6	0.16
***SLGR-12	3/4	19.1	1.30	33.0	4000	275.8	10000	689.5	5.00	127.0	0.41
***SLGR-16	1	25.4	1.63	41.4	4000	275.8	10000	689.5	8.00	152.4	0.65



SLITHER® 4,000 PSI HIGH BURST SLSHBK, SLLHBK Series



A yellow seamless thermoplastic tube, single or double high tensile synthetic fiber braid reinforcement and abrasion resistant **slick** black polyurethane cover.


Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +160°F (+71°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLSHBK-08	1/2	12.7	0.87	22.1	4000	275.8	12000	827.4	3.00	76.2	0.20
SLLHBK-08	1/2	12.7	0.80	20.3	4000	275.8	16000	1103.2	4.00	101.6	0.15
SLLHBK-10	5/8	15.9	0.91	23.0	4000	275.8	12000	827.4	4.00	101.6	0.16



SLITHER® 5,000 PSI SLRD Series



A yellow seamless thermoplastic tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant **slick** red polyurethane cover. Note: Series SLRD-08 has a single high tensile synthetic fiber braid.

Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +160°F (+71°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLRD-04	1/4	6.4	0.50	12.6	5000	344.7	12500	861.8	2.50	63.5	0.05
SLRD-06	3/8	9.7	0.65	16.5	5000	344.7	12500	861.8	3.00	76.2	0.13
SLRD-08	1/2	12.8	0.80	20.2	5000	344.7	12500	861.8	4.00	101.6	0.13

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.